

- Different vend modules (to combine) for individual requirements
- Maximum flexibility by modular structure
- Easy programming using selection button sequence
- Electronic control and data-recording
- Energy management by real time clock
- Electronically controlled forced air-cooling
- 24 V D/C motors



Model	VDI 609
Selections / max. modules	10 / 7
Max. product length (mm),	368 ¹ , 350 ²
Max. product Ø (mm)	72 ¹ , 95 ²

Capacities per module:	Narrow S. ¹	Wide S. ²	Flapper ³
Can 0,33 l	51	88	48
PET bottle 0,50 l	17	28	--
PET bottle 1,00 l	--	24	--
Carton brick pack 0,25 l	--	--	84
brick pack 0,33 l	--	--	60
0,33 Module	Max. H x W (in mm): 143 x 69,85		
0,5 Module	Max. H x W (in mm): 177,8 x 69,85		

Dimensions and weights:			
Width module (mm)	120 ¹	132-185 ²	175 ³
Available interior space (mm)	935		
H x W x D (cabinet mm)	1830 x 1010 x 815		
Weight	355 kg		

Performance data:	
Refrigeration	0,899 kW
Power supply	230 V / 50 Hz
Max. power consumption	820 W

Control	Executive; MDB
Cabinet	Zinc coated steel, powder painted

Standard:	Options:
Black cabinet	Cabinet colour on request
5 digit display	Two-line LCD display
Safety coin return	Security cash system
Anti-vandalism panel in selection button area	Safety sliding coin insert
Cut out for validator or alternative payment system	Anti-rain kit IP 34
Lock	Loading rack
Choice of neutral front poster	DEX / UCS interface
	Special coded lock
	Individual graphics



SandenVendo GmbH | Spangerstrasse 22 | D-40599 Düsseldorf
 Fon: +49 (0)211-740 39-0 | Fax: +49 (0)211-748 85 41
 Web: www.SandenVendo.com | e-Mail: infosvg@sandenvendo.com